



Nedo ACCEPTOR 2 digital with mm display

The new laser receiver ACCEPTOR 2 digital with mm display shows digitally the divergence of the zero line of the laser receiver from the laser plane of the rotating laser. With the mm display, height differences during levelling can be read off directly – without calculation.

Features:

- Sturdy laser receiver for all rotating lasers with red laser beam
- mm display
- Large detector field of 50 mm length
- Large LC display on front and back
- Bright LEDs
- Adjustable signal tone
- Automatic switch-off
- Strong magnets for fastening to steel girders
- Bubble for exact alignment
- Heavy-duty receiver holder of metal

Technische Daten:

- Accuracy switchable, ± 1 mm, ± 4 mm and ± 6 mm
- Working range \varnothing 550 m (depends on laser)
- Protection class: IP 67
- Power supply 2 x 1.5 V batteries (AA) or rechargeable batteries (NiMH)
- Operation duration up to 120 h

Ref.-No. 430 338



Optional Accessory:

Multifunctional rod clamp with patented quick clamp and batter board function

Features:

- Quick and easy attachment with the quick clamp
- Flat positioning of the laser receiver on a wall
- Around-the-corner applications are no problem for the multifunctional receiver holder
- Quick and easy attachment to the batter board

Ref.-No. 062 247



Technical data subject to change