



Laser Receiver COMMANDER 2 H2N+/H2N



Features:

- Extremely robust laser receiver for all rotating lasers with red laser beam
- Integrated radio remote control for the rotating lasers PRIMUS 2 H2N / H2N+
- mm-display
- Heavy-Duty rod clamp made of diecast aluminium
- Large detector field with 70 mm length
- Large LC display on front and back
- Bright LED display
- Adjustable volume
- Automatic switch-off
- Display of remaining battery power
- Easy to handle

Ref.-No.	430 371 COMMANDER 2 H2N
Ref.-No.	430 374 COMMANDER 2 H2N+
Accuracy	switchable, $\pm 0,5$ mm, ± 1 mm, ± 2 mm and ± 4 mm
Working range	\varnothing 700 m (depends on laser)
Length of detector field	70 mm
Reception angle	$\pm 50^\circ$
Protection class	IP 66
Operating temperature	-20°C to $+50^\circ\text{C}$
Power supply	3 x 1.5 V batteries (AA) or rechargeable batteries (NiMH)
Operation duration	up to 100 h



Technical data subject to change



Nedo®

Precise surveying and measuring

Nedo GmbH & Co. KG
Hochgerichtstrasse 39-43
D-72280 Dornstetten

Phone +49 (0) 7443 24 01-0
Fax +49 (0) 7443 24 01-45

info@nedo.com www.nedo.com